

Speed Queen

ON-PREMISE

WASHER-EXTRACTORS

20 lb (9 kg) WASHER-EXTRACTOR

30 lb (14 kg) WASHER-EXTRACTOR

40 lb (18 kg) WASHER-EXTRACTOR

60 lb (27 kg) WASHER-EXTRACTOR

80 lb (36 kg) WASHER-EXTRACTOR

125 lb (57 kg) WASHER-EXTRACTOR



Speed Queen®

BUILT BETTER TO LAST LONGER

LET SPEED QUEEN LEAD THE WAY...

As America's largest commercial laundry equipment manufacturer, Speed Queen stands for quality, convenience, and efficiency. We've integrated innovative technology with proven commercial quality to provide on-premise laundries with state-of-the-art, cost effective laundry units. Since 1908 we have been committed to our tradition of quality products, backed by superior customer service.

MicroMaster2™ System

Today's on-premise laundry rooms need laundry equipment that is flexible, reliable, and delivers excellent cleanability every time. The MicroMaster2 Laundry System from Speed Queen does just that. Speed Queen has developed a system of washer-extractors and tumblers that work in harmony with each other to fulfill these basic needs and exceed expectations.

CLEANABILITY

Linens last longer when they receive the right care. MicroMaster2 washer-extractors combine cycle flexibility with programmable water temperatures for excellent fabric care and more efficient usage of chemical supplies. And a reversing option on the MicroMaster2 tumblers prevents tangles in large loads. Now sheets, blankets, and other oversized items stay separated and dry evenly.

flexibility

The MicroMaster2 Laundry System is designed with versatile programming for a wide range of laundering options. Together the washer-extractors and tumblers have over 30 factory preset or customized cycles to choose from. Once programmed, your laundry results are the same no matter who does the laundry or when.



RELIABILITY

At Speed Queen we're confident that our washer-extractors and tumblers are built better to last longer, and we are offering a three year limited warranty to prove it.*

WASHER-EXTRACTORS



Large Door Opening

The large door opening makes loading and unloading fast and easy. Our heavy-duty stainless steel door features vacuum tight



sealing to keep water inside the machine where it belongs. Constructed with heat-treated, shatter-proof glass and boasting a secure lock, our door enables operators to safely watch the wash process.

Heavy-Duty Bearings and Trunion Assembly

Designed to withstand commercial use, our heavy-duty bearings provide trouble free, long life.

Heavy-Duty Construction

Durable 304 stainless steel cabinet front, sides and top, as well as inner and outer tubs, won't corrode, chip, crack or pit in normal use, and they're extremely rust resistant. Our heavy-duty Gamma A-Frame stands up to even the toughest laundry conditions, keeping Speed Queen washer-extractors durable for years to come.



Superior Serviceability

Speed Queen's removable top and front panel are designed for minimum down time and ease of service. Troubleshooting electrical systems and accessing drain valve components are easier than ever.



Automatic Supply Injection

The benefits of our Automatic Supply Injection System



are reduced waste of detergents and more consistent laundry results. The self-cleaning, multi-compartment dispenser automatically dispenses detergent for prewash, detergent for main wash and fabric softener for final rinse. In addition, tubing and electrical connections are provided on the rear of the machine for easy on-site hook-up to a liquid central supply system.

Heating Options

Speed Queen models can heat water via steam or electricity. You choose the heating option that best fits your on-premise laundry room.

Control Options



MicroMaster2™ Control

With Speed Queen's state-of-the-art MicroMaster2 Laundry System your laundry room will operate more efficiently. The system offers users 30 programs, all of which can be customized to meet the specific needs of the laundry operation. MicroMaster2 also boasts a rapid advance function, which enables operators to jump the cycle to the end, add extra items to the load, and restart the machine where it left off. Other features include cycle time remaining display, cycle counter, test cycle for diagnostics, half speed wash for delicate items and a cool down rinse.



“B” 8 Cycle Programmable Micro Control

The B-Micro control is designed to offer you eight pre-programmed cycles. These cycles can be customized to fit your specific needs. By customizing your cycles you can significantly reduce water consumption. Turnaround time also is improved by doing the maximum amount of cleaning in the smallest amount of time. The B-Micro also is very easy to operate. A separate start pad has been added for convenience and cycle symbols have been designed to match garment care labels.



“M” 4 Cycle Electro-Mechanical Control

Four preset wash formulas offer a choice of hot, for heavy soil and whites; warm, for medium soil and whites; warm, for light soil and permanent press; cold, for all cold water wash, delicates, knits and lightly soiled fabrics. These four cycle selections vary length of wash, wash action and length of final spin. You can depend on Speed Queen to get clothes their cleanest day after day.

(Available only on 20 - 60 lb)

3 YEAR LIMITED WARRANTY



At Speed Queen, we're confident that our washer-extractors are built better to last longer and we're offering the following limited warranty to prove it:

Through three years*

Any part on the entire machine.

Through five years*

The bearings and bearing seal assembly.

Through five years*

Frame, cylinder and shaft assembly.

* Parts only. Labor not included.

See Speed Queen Warranty Bond for specifics.

WASHER-EXTRACTOR SPECIFICATIONS

	SC20	SC30	SC40	SC60	SC80	SC125
Capacity - lb (kg)	20 (9)	30 (13.6)	40 (18)	60 (27)	80 (36)	125 (56.7)
Width - in (mm)	26" (660)	29" (737)	30 5/8" (778)	34 1/16" (865)	41 1/2" (1054)	48" (1219)
Height - in (mm)	42 7/8" (1089)	45 7/8" (1165)	47 1/4" (1200)	50 13/16" (1291)	56 7/8" (1444)	70 1/2" (1791)
Depth* - in (mm)	29 13/16" (757)	34 13/16" (884)	40" (1016)	42 15/16" (1091)	52" (1321)	56 3/4" (1441)
Cylinder Diameter - in (mm)	21" (533)	24" (610)	26 1/4" (667)	30" (762)	36" (916)	42" (1067)
Cylinder Depth - in (mm)	13 3/4" (349)	16" (406)	20 1/4" (514)	22" (559)	22" (559)	24" (610)
Cylinder Volume - cu. ft. (liters)	2.76 (78.1)	4.19 (118)	6.34 (180)	9.0 (255)	12.4 (354)	19.20 (544)
Door Opening Size - in (mm)	11 5/8" (295)	14 11/32" (364)	16 1/4" (413)	16 1/4" (413)	18 1/2" (470)	20" (508)
Door Bottom to Floor - in (mm)	14 3/8" (366)	14" (356)	14 1/2" (368)	15" (381)	17 3/4" (451)	28 1/8" (511)
Wash Speed - RPM	2-speed 6-speed	49 N/A	51 26/51	44 24/43	N/A 22/41	N/A 27/37
Extract Speed - RPM	2-speed 6-speed	464 N/A	491 328/478/614	469 307/447/573	N/A 280/408/537	N/A 260/380/485
G-Factor	2-speed 6-speed	83.1 N/A	73.3 N/A	89.8 40/85/140	93.8 40/85/147	N/A 40/85/147
Water Inlet Conn. - in (mm)	3/4" (19)	3/4" (19)	3/4" (19)	3/4" (19)	3/4" (19)	1" (25)
Steam Inlet Conn. - in (mm)	1/2" (13)	1/2" (13)	1/2" (13)	1/2" (13)	1/2" (13)	3/4" (19)
Drain Diameter - in (mm)	2" (52)	2" (52)	3" (76)	3" (76)	3" (76)	3" (76)
Drain Height to Floor - in (mm)	4 3/8" (114)	4" (100)	4 3/4" (121)	5" (127)	5 3/4" (146)	11 1/16" (146)
Motor Wash - HP (kW)	2-speed 6-speed	.15 (.11) N/A	.24 (.18) N/A	.40 (.30) .40 (.30)	.55 (.41) .55 (.41)	N/A N/A
Motor HP Extract - HP (kW)	2-speed 6-speed	.74 (.55) N/A	1.34 (1) N/A	1.8 (1.3) 1.8 (1.3)	2.7 (2.01) 2.7 (2.01)	5 (3.73) 5 (3.73)
Voltage/Hz/Phase**	B	120/60/1 20-15	N/A	N/A	N/A	N/A
Circuit Breaker-FLA amp	C	380-415/50/3 15-2	380-415/50/3 15-2	380-415/50/3 15-2	380-415/50/3 15-2	N/A
	D	220-240/50/3 15-4	220-240/50/3 15-3	220-240/50/3 15-3	220-240/50/3 15-4	N/A
	E	220-240/50/1 15-4	220-240/50/1 15-5	N/A	N/A	N/A
	F	440-480/60/3 15-2	440-480/60/3 15-2	440-480/60/3 15-5	440-480/60/3 15-3	N/A
	J	200/50/3 15-3	200/50/3 15-2	200/50/3 15-2	200/50/3 15-5	N/A
	N	N/A	N/A	N/A	N/A	440-480/50-60/3 15-7
	O	208-240/60/3 15-3	208-240/60/3 15-4	208-240/60/3 15-3	208-240/60/3 15-4	N/A
	P	N/A	N/A	N/A	N/A	380-415/50-60/3 15-4
	Q	N/A	N/A	N/A	N/A	200-240/50-60/3 15-7
	X	N/A	N/A	N/A	200-240/50-60/1-3 20-9	N/A
	Y	208-240/60/1 15-6	208-240/60/1 15-10	208-240/60/1 30-14	N/A	N/A
Shipping Dimensions - in (mm)	H	51" (1295)	53 1/2" (1359)	56 1/2" (1422)	58 1/2" (1486)	62 1/2" (1588)
	W	29" (737)	30 1/2" (774)	32" (813)	36" (914)	48" (1219)
	D	32 1/2" (826)	37 1/2" (953)	41" (1041)	44 1/2" (1130)	56" (1422)
Net Weight - lb (kg)	353 (160)	496 (225)	686 (311)	811 (368)	1346 (610)	2316 (1053)
Standard Shipping Wt. - lb (kg)	373 (169)	519 (235)	710 (322)	838 (380)	1420 (644)	2421 (1100)
Crate Shipping Wt. - lb (kg)	461 (209)	600 (272)	810 (367)	947 (430)	1545 (701)	2701 (1228)
Agency Approvals***	CE, ETL, ETL _C	CE, ETL, ETL _C	CE, ETL, ETL _C	CE, ETL, ETL _C	ETL, ETL _C	ETL, ETL _C

* Overall Depth includes drain pipe and door handle.

** Standard domestic voltage 208-240/60/3 (3-wire), standard international 380-415/50/3 (4-wire). Circuit breaker and amp draw data shown is for standard voltage models without auxiliary heat. Consult factory for availability of 440-480 models and other configurations. Manufacturer strongly recommends using a circuit breaker instead of fuses. Use 3-pole circuit breakers for 3-phase machines.

*** Agency Approval.

Due to continuous product improvements, design and specifications subject to change without notice. The quality management systems at all Alliance Laundry Systems manufacturing facilities are registered as ISO 9001:2000 compliant.

© Copyright 2006 Alliance Laundry Systems LLC



www.speedqueen.com

Speed Queen.
Alliance Laundry Systems